



## Syntrans Multivehicle 75W-90

Manual Transmission Fluid

### Description

Castrol Syntrans Multivehicle 75W-90 is a full synthetic SAE 75W-90 manual transmission fluid recommended for most manual transmissions where API GL-4 lubricants are required. It has been successfully used as a problem solver for low temperature shiftability issues in the manual transmissions of a number of manufacturers.

### Advantages

- Excellent synchroniser performance giving extended synchroniser life and shift comfort.
- Exceptional cold flow properties giving smoother gear shift at low temperatures.
- High shear stability giving a constant viscosity during oil life and noise reduction.
- Excellent thermal and oxidative stability for transmission cleanliness and longer oil life.
- Temperature reduction in operation prolongs the life of lubricant and aids fuel efficiency

### Typical Characteristics

Name	Method	Units	Syntrans Multivehicle 75W-85
Density @ 15C	DIN 51757	g/ml	0.871
Viscosity, Kinematic 100C	DIN 51562	mm <sup>2</sup> /s	11.4
Appearance	Visual	-	Bright & Clear-
Viscosity, Brookfield @ -40C	ASTM D2983	mPa.s (cP)	30000
Pour Point	ASTM D97	°C	-51
Flash Point, COC	ASTM D92	°C	228

### Product Performance Claims

API GL-3 / GL-4

Syntrans Multivehicle 75W-90  
22 Jan 2011

Castrol, Syntrans Multivehicle 75W-90 and the Castrol logo are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.